AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

Claims 1-10 (canceled).

Claim 11 (currently amended): A mounting structure for a fuel pump of a vehicle engine, the mounting structure comprising:

a fuel pump assembly including a cylindrical pump body and a filter coupled with a suction end of the pump body;

a fuel tank arranged to straddle a body frame of a vehicle;

a housing enclosing the cylindrical pump body, a flange section of the housing arranged to abut an outside area surrounding an opening in a the fuel tank; and

a mounting plate arranged to cover the flange section on an outside of the fuel tank, the fuel pump assembly arranged to be fixed to the opening through the mounting plate and the flange section; wherein

an axis of the cylindrical pump body extends generally parallel to a mounting surface of the mounting plate; and

the cylindrical pump body and the filter are arranged to overlap each other in a plan view of the vehicle;

the opening is arranged in a side wall surface of the fuel tank, the mounting plate is attached to the opening of the side wall surface of the fuel tank; and

the mounting plate and the cylindrical pump at least partially overlap each other in a lateral side view of the vehicle.

Claim 12 (canceled).

Claim 13 (currently amended): The mounting structure for a fuel pump of a vehicle engine according to Claim 1211, wherein the opening is arranged in the side

Application No. 10/596,635 May 8, 2009 Reply to the Office Action dated February 17, 2009 Page 3 of 10

wall surface of the saddle type fuel tank, and the filter is disposed below the cylindrical pump body.

Claim 14 (currently amended): The mounting structure for a fuel pump of a vehicle engine according to Claim 1211, wherein the opening has an elliptical shape, and a longitudinal axis of the opening extends generally horizontally and generally parallel to the axis of the cylindrical pump body.

Claim 15 (currently amended): The mounting structure for a fuel pump of a vehicle engine according to Claim 11, further comprising a fuel passage, wherein the fuel passage includes the filter, the cylindrical pump body, and a member through which fuel flows from the filter to the cylindrical pump body, and wherein a portion of the fuel passage is arranged so as to overlap itselfanother portion of the fuel passage.

Claim 16 (previously presented): The mounting structure for a fuel pump of a vehicle engine according to Claim 11, wherein the cylindrical pump body and the filter are spaced apart from each other in a direction normal to the axis of the cylindrical pump body.

Claim 17 (currently amended): A mounting structure for a fuel pump of a vehicle engine, the mounting structure comprising:

a fuel tank arranged to straddle a body frame of a vehicle; and

a fuel pump assembly to be arranged within an inner space of a the fuel tank, the fuel pump assembly including a mounting plate arranged to mount the fuel pump assembly onto the fuel tank, the fuel pump assembly further including:

a cylindrical pump body; and

a filter attached to the cylindrical pump body;

an opening arranged in a side surface of the fuel tank;

Application No. 10/596,635 May 8, 2009 Reply to the Office Action dated February 17, 2009 Page 4 of 10

a housing enclosing the cylindrical pump body, a flange section of the housing arranged to abut an outside area surrounding the opening in the fuel tank, and the mounting plate extends over the flange section to fix the flange section to the fuel tank; wherein

the cylindrical pump body is arranged such that an axis of the cylindrical pump body extends along a mounting surface of the mounting plate; and

the filter is arranged such that at least a portion of the filter is spaced away from the cylindrical pump body in a radial direction of the cylindrical pump body;

the mounting plate is attached to the opening of the side surface of the fuel tank; and

the mounting plate and the cylindrical pump at least partially overlap each other in a lateral side view of the vehicle.

Claim 18 (canceled).

Claim 19 (previously presented): The mounting structure for a fuel pump of a vehicle engine according to Claim 17, further comprising a fuel pipe having a first end with which the cylindrical pump body is coupled, a trunk portion of the fuel pipe bending toward the filter, and a second end with which the filter is coupled, wherein a fuel flow direction in the cylindrical pump body and a fuel flow direction in the filter are reversed from each other.

Claim 20 (currently amended): The mounting structure for a fuel pump of a vehicle engine according to Claim 1817, wherein the opening has an elliptical shape, and a longitudinal axis of the opening extends generally horizontally and generally parallel to the axis of the cylindrical pump body.

Claim 21 (previously presented): A vehicle comprising the mounting structure for a fuel pump according to Claim 11.

Application No. 10/596,635 May 8, 2009 Reply to the Office Action dated February 17, 2009 Page 5 of 10

Claim 22 (previously presented): A vehicle comprising the mounting structure for a fuel pump according to Claim 17.